

APPENDIX A – SUPPLEMENTAL INFORMATION FOR SELECTION OF PRGS EAST WATERWAY OPERABLE UNIT FEASIBILITY STUDY

Commented [LR1]: Key:

Yellow = Port deleted text that EPA added

Green = Port edited EPA text slightly

Blue = Port rejected EPA deletions

No color = other Port edits

Prepared for

Port of Seattle

Prepared by

Anchor QEA, LLC

720 Olive Way, Suite 1900

Seattle, Washington 98101

November 2017

APPENDIX A TABLE OF CONTENTS

- Part 1 Compliance with Sediment Management Standards**
- Part 2 Development of Sediment PRGs for PCBs in Fish**

PART 1: COMPLIANCE WITH SEDIMENT MANAGEMENT STANDARDS

TABLE OF CONTENTS

[TOC \O "1-4" \H \Z \U][TOC \Z \O "1-4" \U \H]

List of Tables

| | |
|---------|--|
| Table 1 | Areas and Post-construction Concentrations for Maximum Possible Remediation Evaluation |
| Table 2 | Technical Possibility Lines of Evidence |

List of Figures

| | |
|----------|--|
| Figure 1 | Areas and Offsets for Maximum Possible Remediation Evaluation |
| Figure 2 | Conceptual Cross Section Showing Maximum Possible Remediation for Terminal with Keyway |

1 INTRODUCTION

The Feasibility Study (FS) for the East Waterway (EW) Operable Unit (OU) has been developed under the regulatory framework of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA). Consistent with CERCLA requirements, the selected alternative must substantively comply with applicable or relevant and appropriate requirements (ARARs), which include portions of the Washington State Sediment Management Standards (SMS). The SMS are the Washington State standards for remediating sediments under the Model Toxics Control Act (MTCA). This appendix provides a brief description of the methods and procedures for establishing cleanup levels under the SMS, and also discusses how the EW alternatives developed under CERCLA ~~will~~ comply with the SMS requirements.

Formatted: Strikethrough, Highlight

Formatted: Highlight

This appendix is provided solely for the purpose of evaluation of the remedial action alternatives in the FS, and provides a projection of how these alternatives may address compliance with those portions of the SMS that are anticipated to be ARARs based on current sediment quality conditions after remediation. Only the final State Environmental Protection Agency (SEPA) ARARs for the OU OU period of review (POD), compliance with the relevant portions of the SMS will be determined by EPA during or at the completion of the remedial action.

The preliminary remediation goals (PRGs) presented in Section 4 of the FS were developed to comply with portions of the SMS that are ARARs under CERCLA, including the determination of cleanup levels¹ under Washington Administrative Code (WAC) 173-204-560. The SMS cleanup level determination is performed by determining the sediment cleanup objectives (SCO; discussed in Section 2 of this appendix) and the cleanup screening levels (CSL; discussed in Section 3 of this appendix). The cleanup levels are initially set at the SCO. If the SCO is not technically possible to attain, or would result in net adverse environmental impacts, then the cleanup level can be adjusted up to the CSL.

¹ For the purposes of this appendix only, the SMS term “cleanup level” is considered analogous to the CERCLA term “PRG” used in the main text of the FS. This appendix sometimes uses the term “cleanup level” for consistency with the SMS. In other contexts, these terms may not have the same meaning.

For several contaminants of concern (COCs) in the FS, the SCO-based PRG has PRGs have been established at their natural background concentration, because risk-based SCO concentrations are lower than the natural background concentration. This is consistent with both SMS and CERCLA. Although both SMS and CERCLA allow for a regional background-based GSL value to be considered as well, there is no EPA-approved regional background concentration determined for the EW area. As described in Section 4, FS model predictions developed by In the Port absence of Seattle (Port) indicate long-term post-cleanup concentrations of total polychlorinated biphenyls (PCBs) and dioxins/furans that are higher than the natural regional background values, cleanup levels (i.e., PRGs) for these COCs are based PRGs (e.g., see FS Section 9).³⁴ on the SCO in the EW FS. For some of these COCs, the modeling indicated that the SCO is not technically possible to achieve. Long-term monitoring data will allow for a more informed evaluation of technical possibility.

For the purpose of informing alternatives in the FS (Section 4.1.1), EPA requested that additional modeling of a “hypothetical maximum remediation scenario” be conducted to estimate the lowest concentration that could be achieved as a result of remedy implementation. This modeling was conducted to estimate post-construction concentrations and was not conducted for purposes of predicting the long-term outcome of any of the alternatives. The hypothetical maximum remediation scenario is based on a series of estimates using the best available data; however, these estimates are inherently uncertain. The modeling was based on FS-level evaluations, and contains uncertainty insofar as detailed engineering design has not been conducted to inform the input parameters that affect the post-construction concentrations. While sensitivity and bounding analysis was completed for the long-term model predictions used in comparing FS alternatives, it was not conducted for the hypothetical maximum remediation scenario analysis. Nonetheless, the analysis provides information that could be used to evaluate whether it is technically possible

³⁴ Note that none of the alternatives is predicted by the Port's FS models to achieve the SCO for these chemicals; therefore, this appendix applies equally to any of the alternatives, if selected.

³⁵ Note that the Port's FS models are based upon estimated values for contaminant inputs and removal and do not include decreases in inputs due to source control. Uncertainties associated with the model are discussed in Appendix J.

Formatted: Highlight

Formatted: Highlight

Formatted: Not Strikethrough, Highlight

Formatted: Highlight

Formatted: Not Strikethrough, Highlight

Formatted: Highlight

Formatted: Not Strikethrough, Highlight

Formatted: Not Strikethrough, Highlight

to achieve natural background-based PRGs, and it provides additional information that EPA could consider for a potential future adjustment of cleanup levels under SMS or for a technical impracticability (TI) waiver under Section 121(d)(4)(C) of CERCLA, 42 U.S.C § 9621(d)(4)(C).

As described in Section 9 of the FS, model predictions indicate that long-term post-cleanup concentrations of total polychlorinated biphenyls (PCBs) and dioxins/furans will be higher than the natural background-based PRGs.⁵³ The modeling includes some assumptions for future source control for the EW and Lower Duwamish Waterway (LDW), but not for the upper Duwamish and Green Rivers, all of which contributes to uncertainty of predictions. While the analysis indicates that it will not likely be technically possible to achieve all natural background-based PRGs in the EW, the cleanup will still achieve the MTCA/SMS ARARs. This appendix discusses different mechanisms for SMS compliance.

Commented [HA2]: For consistency and accuracy – this is how they/we say it later in this appendix.

Formatted: Highlight

Formatted: Highlight

Based on preliminary evaluations, the EW OU cleanup is expected to comply with MTCA/SMS for protectiveness of human health for direct contact (remedial action objective [RAO] 2), protection of the benthic community (RAO 3), and protection of higher trophic level organisms (RAO 4) by achieving the PRGs for these RAOs. Following modeling of the hypothetical maximum remediation scenario at the completion of cleanup implementation and modeling of long-term site-wide concentrations following source control and remediation efforts, of LDW and EW lateral inputs both predict that surface sediments in the EW OU are will not currently predicted under the Port's model to attain all natural background-based PRGs for protection of human health for seafood consumption (RAO 1). This is based on estimates of long-term site-wide concentrations are driven primarily by the ongoing contribution of elevated concentrations from diffuse, nonpoint sources of contamination that contribute to regional background concentrations. However, achieving the MTCA/SMS ARARs may nonetheless occur in one of two ways:

⁵ Note that none of the alternatives is predicted by the Port's FS models to achieve the SCO for these chemicals; therefore, this appendix applies equally to any of the alternatives, if selected.

⁵³ Note that the Port's FS models are based upon estimated values for contaminant inputs and removal and do not include decreases in inputs due to source control. Uncertainties associated with the model are discussed in Appendix J.

- Post-remedy monitoring may demonstrate sediment concentrations lower than currently predicted by the model current model predictions, and PRGs identified in this FS may be attained for certain chemicals in a reasonable restoration timeframe. If necessary, the restoration timeframe needed to meet the PRGs could be extended by the United States Environmental Protection Agency (EPA) if EPA, where consistent with CERCLA. In making such a determination, EPA may take into account the substantive criteria for a Sediment Recovery Zone (SRZ), as provided by the SMS at WAC 173-204-590(3) (see Section 5 of this appendix).
- Sediment cleanup levels (SCLs) may be adjusted upward if regional background levels are established for the geographic area of the EW (see Section 4 of this appendix), and EPA determines these levels are appropriate for use at the EW CERCLA site. Considering that a regional background value has not yet been determined for the EW, such adjustments could occur in the ROD (before remediation) or subsequently as part of a ROD amendment or Explanation of Significant Differences (ESD) (during or after remediation). Consistent with the bullet above, the restoration timeframe needed to meet the SCLs could be extended by EPA where consistent with CERCLA requirements for a reasonable restoration timeframe.

In addition, following remediation and long-term monitoring, In addition to these two potential MTCA/SMS ARARs compliance mechanisms, a final site remedy can be achieved under CERCLA if EPA determines that no additional practicable actions can be implemented under CERCLA to meet certain MTCA/SMS ARARs, EPA may issue such that a ROD Amendment or ESD providing the basis for a technical impracticability (TI) waiver would be warranted for specified MTCA/SMS those ARARs under Section 121(d)(4)(C) of CERCLA, 42 U.S.C. § 9621(d)(4)(C).

Because it is not known whether, or to what extent, the SMS ARARs for total PCBs and dioxin/furans will be achieved in the long term, it is not possible at this time to determine with certainty whether the FS alternatives will attain the SMS ARARs the selection of which of the two compliance mechanisms described above (either meeting the natural background PRG in a reasonable restoration timeframe, or upwardly adjusting the SCL to regional

background and meeting it in a reasonable restoration timeframe), is not identified at this time.

The rest of this appendix provides additional detail regarding establishing SCO (Section 2) and CSL (Section 3) concentrations, potentially upwardly adjusting cleanup levels in the future (Section 4), and implementation of an SRZ (Section 5). Section 6 provides a summary of the methods to that may be used to comply with the SMS ARARs.

2 SEDIMENT CLEANUP OBJECTIVES

The SMS outline procedures for establishing the lower bound for cleanup levels, called the SCO. Multiple exposure pathways, natural background concentrations, and practical quantitation limits (PQLs) are all considered when determining the SCO, as follows:

WAC 173-204-560 (3) Sediment cleanup objectives. The sediment cleanup objective for a contaminant shall be established as the highest of the following levels:

(a) The lowest of the following risk-based levels:

(i) The concentration of the contaminant based on protection of human health as specified in WAC 173-204-561(2);

(ii) The concentration or level of biological effects of the contaminant based on benthic toxicity as specified in WAC 173-204-562 or 173-204-563, as applicable;

(iii) The concentration or level of biological effects of the contaminant estimated to result in no adverse effects to higher trophic level species as specified in WAC 173-204-564; and

(iv) Requirements in other applicable laws;

(b) Natural background; and

(c) Practical quantitation limit.

As summarized in Tables 4-3 and 4-4 of the FS, RAOs were established under CERCLA for these FS to be consistent with WAC regulations:

- Risk-based threshold concentrations (RBTCs) associated with RAOs 1 and 2 were established to be consistent with WAC 173-204-560(3)(a)(i)
- RBTCs associated with RAO 3 were established to be consistent with WAC 173-204-560(3)(a)(ii)
- RBTCs associated with RAO 4 were established to be consistent with WAC 173-204-560(3)(a)(iii)
- Natural background concentrations were established to be consistent with WAC 173-204-505(11)
- PQLs were established to be consistent with WAC 173-204-505(14)

The Washington State Department of Ecology (Ecology) Sediment Cleanup User's Manual (SCUM) II (Ecology 2017) is not an ARAR under CERCLA, although some portions of SCUM II may be evaluated as "to be considered" (TBC) criteria. As discussed in Section 4 of the main body of the FS, EPA has prescribed other methods for determining natural background concentrations for establishing PRGs in compliance with CERCLA (e.g., see FS Table 4-2). Solely for informational and comparison purposes, it is noted that in SCUM II, the SCO based on natural background for total PCBs is listed as 3.5 micrograms per kilogram ($\mu\text{g/kg}$) dry weight (dw) and the SCO based on the PQL for dioxins/furans is listed at 5 nanograms (ng) toxic equivalent (TEQ)/kg dw, because these are the highest of the three SCO levels for these compounds. The arsenic SCO is also established at natural background, but SCUM II defines the Ecology-determined natural background concentration for arsenic to be 11 milligrams per kilogram (mg/kg), which would be achievable based on best-estimate FS model results. However, EPA does not consider these values to be ARARs or TBCs.

3 CLEANUP SCREENING LEVELS

The SMS outline similar procedures for establishing the upper bound for cleanup levels, called the CSL:

WAC 173-204-560 (4) Cleanup screening levels. The cleanup screening level for a contaminant shall be established as the highest of the following levels:

(a) The lowest of the following risk-based levels:

(i) The concentration of the contaminant based on protection of human health as specified in WAC 173-204-561(3);

(ii) The concentration or level of biological effects of the contaminant based on benthic toxicity as specified in WAC 173-204-562 or 173-204-563, as applicable;

(iii) The concentration or level of biological effects of the contaminant estimated to result in no adverse effects to higher trophic level species as specified in WAC 173-204-564; and

(iv) Requirements in other applicable laws;

(b) Regional background as defined in subsection (5) of this section; and

(c) Practical quantitation limit.

RBTCs associated with the CSL (excess cancer risk of 10^{-5} or hazard quotient of 1) are presented in FS Table 3-13 and are well below the SCOs for total PCBs and dioxins/furans.

The SMS defines regional background as follows:

WAC 173-204-505(16)

Regional background means the concentration of a contaminant within a department-defined geographic area that is primarily attributable to diffuse nonpoint sources, such as atmospheric deposition or storm water, not attributable to a specific source or release. See WAC 173-204-560(5) for the procedures and requirements for establishing regional background.

The CSL for total PCBs and dioxins/furans may be based on regional background concentrations, once established. However, in the absence of regional background concentrations deemed by EPA to be suitable for use at the EW [REDACTED], and

because the risk-based levels are below the [REDACTED], the CSL has not been established for total PCBs or dioxin/furans.

In the future, Ecology may develop an approach to collect additional information to establish regional background for the Lower Duwamish Waterway (LDW), but Ecology has not yet suggested how this may be applied to the EW. EPA may consider this approach and information once they have been provided by Ecology.

4 ADJUSTMENT OF CLEANUP LEVELS

As discussed previously, because regional background concentrations have not been determined for the FW and the upper bound for the cleanup level (the CSL) has not been determined, the cleanup levels in the FS are set at the SCO for total PCBs and dioxins/furans. However, if regional background concentrations suitable for use at the EW OU are established, then, following the SMS, the cleanup levels may be adjusted upward by EPA based on the following site-specific factors:

WAC 173-204-560(2)(a)

(ii) Upward adjustments. The sediment cleanup level may be adjusted upward from the sediment cleanup objective based on the following site-specific factors:

- (A) Whether it is technically possible to achieve the sediment cleanup level at the applicable point of compliance within the site or sediment cleanup unit; and
- (B) Whether meeting the sediment cleanup level will have a net adverse environmental impact on the aquatic environment, taking into account the short- and long-term positive effects on natural resources, habitat restoration, and habitat enhancement and the short- and long-term adverse impacts on natural resources and habitat caused by cleanup actions

The following sections discuss the site-specific factors that could be considered by EPA to adjust the cleanup levels from the SCO.

4.1 Technical Possibility

The SMS define "technical possibility is defined in the SMS" as follows:

WAC 173-204-505(23)

"Technically possible" means capable of being designed, constructed and implemented in a reliable and effective manner, regardless of cost.

Considerations for upward adjustments of cleanup levels based on technical possibility are provided in Ecology's SCUM II guidance document, which states that upward adjustments of cleanup levels under WAC 173-204-560(2)(a)(ii)(A) should be based on "whether it is

Commented [A3]: Although we don't disagree that maintenance of the CUL should be considered in a "technical possibility" determination; this provision in SCUM II is not an ARAR.

technically possible to achieve *and maintain* the cleanup level at the applicable point of compliance." [emphasis added] Although SCUM II is not an ARAR, this provision of Ecology's guidance is [redacted] similar to EPA's environmental criteria requiring long-term

This section first estimates the lowest technically possible concentrations that could be achieved in the EW immediately following construction for a hypothetical maximum remediation scenario. It (Section 4.1.1). The post-construction concentration modeling for the hypothetical maximum remediation scenario was based on [redacted] FS-level evaluations using best available data, but contains uncertainty, as detailed engineering design has not been conducted to inform the input parameters that affect the post-construction concentrations, and no sensitivity or bounding analysis was completed. Additional design evaluations will be conducted in the future following the ROD.

This appendix also evaluates what is technically possible to maintain in the long term following construction (Section 4.1.2). Uncertainty also exists regarding long-term concentrations, including future conditions following source control, as described in FS Appendix J.

The combination of these two evaluations by the Port the hypothetical maximum remediation scenario evaluations and the evaluation of what is technically possible to maintain in the long term following construction may be used by EPA to evaluate technical possibility. This analysis is developed for FS purposes only; it contains numerous assumptions about future conditions that cannot be reliably estimated at this time. It is an evaluation by the Port that is not required to be used for decision-making by EPA, including establishing PRGs or cleanup levels. Technical possibility will be determined based on empirical long-term monitoring data for the selected alternative to comply with the SMS.

4.1.1 Technical Possibility of Hypothetical Maximum Remediation Scenario

The EW is a highly urbanized, commercial waterway with actively used marine transportation infrastructure along most of the shoreline area that limits the remedial activities that can occur. For example, full removal of all contaminated sediment near

structures is not possible without affecting structural stability. As a result, some amount of undisturbed contaminated sediment will in all likelihood remain in near structures following remediation; however, measures to minimize releases from these areas practicably reduce remaining contaminated sediment will be considered in the design phase.

This section describes an FS-level analysis on a hypothetical site-wide dredging scenario to estimate the lowest concentration that may be technically possible to achieve for total PCBs at the completion of construction. The scenario was developed by the Port assuming that all engineered infrastructure such as piers, engineered embankments, keyways, bridges, and the communication cable crossing would remain in place. EPA reviewed some but not all of the input parameters and assumptions used in this model. Removing and reconstructing the infrastructure associated with the EW would require massive modifications (e.g., reconstructing the West Seattle Bridge, temporarily closing important Coast Guard and Port of Seattle terminals, etc.) that would result in excessive disturbance to essential public and private infrastructure. Moreover, this scenario assumed that remediation would be performed by dredging everywhere possible and included residuals management re-dredging passes where practicable to further lower concentrations. Dredging was assumed to be followed by residuals management cover (RMC) in most locations, and was assumed to be followed by in situ treatment with activated carbon in underpier and keyway areas where RMC material could not be placed due to stability concerns and navigation depth requirements.

Note that this hypothetical scenario was created for the purposes of developing alternatives in support of the FS and does not itself represent an alternative in the FS; nor is it intended to make provide definitive statements/predictions regarding future concentrations in the EW. Also note that this analysis estimates concentrations at a single point in time (immediately after construction)—ignoring ongoing mixing, propwash, and incoming sedimentation, and during the decreased loading associated with future source control efforts within the upper Duwamish construction period, and therefore biased low compared to what can be accomplished/achieved in the long-term (Section 4.1.2). The scenario is based on estimates using best available data, but is subject to uncertainty, as detailed design evaluations, including construction sequencing

Formatted: Highlight

and other measures to minimize remaining contaminated sediments, have not been conducted.

To support this analysis, the EW was divided into six areas based on the physical constraints of each (Table 1, Figure 1). Spatially-weighted average concentrations (SWACs) immediately following construction were calculated using the box model evaluation for each as summarized in the following paragraphs. It should be noted two key parameters which have a large influence on model outputs are likely biased high: potential future reductions in bioavailable concentrations of PCBs after in-situ treatment are likely to be higher than estimated in the model, and estimates of incoming sediment concentrations do not account for upstream source control. inputs for each as summarized in the following paragraphs.

Area 1

The first area consists of most of the open-water areas of the waterway (114 acres), and has the fewest structural limitations affecting remediation. In these areas, the assumed remediation scenario was dredging the waterway to the deepest extent of contaminated sediment, followed by two residuals management re-dredging passes (average of 2 feet removal for each), followed by RMC placement. The resulting concentration immediately following construction in surface sediment (top 10 centimeters [cm]) was estimated to be 10 µg/kg dw for total PCBs for this area, based on the dredging residuals calculation methodology presented in FS Appendix B, Part 3A.

Area 2

The second area includes 15 acres of underpier sediments that have limited access and are present on top of slopes comprised of large riprap (see Figure 2). Remediation in these areas is challenging due to access limitations and the presence of hard riprap surfaces and rock interstices. These areas were assumed to be dredged by diver-assisted hydraulic dredging, followed by a thin placement of in situ treatment material to reduce bioavailability of the remaining sediment. The resulting post-construction concentration was estimated to be 290 µg/kg dw for total PCBs. This assumed that an average of 10 cm (3.9 inches) of sediments would remain in place following remediation due to the difficulty of full removal on riprap slopes and within rock interstices, followed by the mixing of 7.6 cm (3 inches) of in situ treatment material (see residuals calculations presented in FS Appendix B, Part 3A). In situ

treatment material was also assumed to reduce the bioavailability of hydrophobic organic compounds such as PCBs by 70% (FS Section 5.3.5), resulting in an estimated effective bioavailable underpier average concentration estimated on a dry-weight basis of 153 µg/kg⁶. Note that in situ treatment is a less proven technology than the others presented in this evaluation and, therefore, in situ treatment is used only in areas where other, more-proven technologies are not feasible or unlikely to be effective, such as under the piers (see Section 7.2.7.1 and 7.8 of the FS). ~~The assumed reduction~~ Reduction in bioavailability of 70% is approximated from available evidence from bench-scale laboratory studies and field demonstrations (FS Section 5.3.5), and is a conservative (low) estimate considering that these studies have consistently shown reductions of 90% subject to 99% uncertainty (Section 2.4 of FS Appendix J).

Area 3

The third area includes 7 acres of keyways that are at the base of the underpier slopes (see Figures 1 and 2). These are rock structures keyed into the toe of the riprap slopes to maintain the stability of the slopes above. The tops of the keyways are situated at the navigation depth of approximately -51 feet mean lower low water, therefore limiting the amount of removal and the amount of clean fill placement that can be performed in these areas. Similar to the underpier areas, these areas were assumed to be dredged to the maximum extent possible without removing riprap, followed by a thin placement of in situ treatment material to reduce bioavailability. For this analysis, dredging was assumed to be performed by standard mechanical means. The resulting post-construction concentration was estimated to be 364 µg/kg dw for total PCBs based on an average of 10 cm (3.9 inches) of sediment remaining following dredging, with a 7.6-cm (3-inch) layer of clean in situ treatment material being placed following dredging. The effective bioavailable average concentration in keyways (using a 70% reduction in dry weight concentrations) was estimated to be 192 µg/kg. Note that ~~Note that the placement of in situ treatment material in keyways presented for this evaluation is hypothetical to support this evaluation; however, some keyway areas are already at the required navigation elevation and placement would not be possible in some areas due to navigation requirements. In addition,~~ long-term effectiveness and stability of

Commented [LR4]: In order to achieve a 3-inch minimum placement thickness, contractors will inevitably place more material to achieve the minimum considering equipment precision and capabilities. The Port cannot decrease berth depths, so this statement is important to maintain.

⁶ Note the dry-weight concentration is intended to estimate bioavailability reduction to support calculation of a site-wide SWAC that considers the benefits of the application of in situ treatment material, but this concentration is not what would be measured on a dry-weight basis following construction.

placement near active berthing areas is highly uncertain because of propeller wash (propwash), but was assumed to be stable for the purpose of this analysis.

Area 4

The fourth area includes 18 acres of structural slope and offset areas where dredge depths will be limited by the geotechnical stability of adjacent slopes (see Figures 1 and 2). In these areas, some contaminated sediment will be left behind; however, these elevation constraints are assumed to still allow the placement of a full RMC layer (i.e., average 9-inch-thick sand layer). The concentration immediately following completion of construction was estimated to be 35 µg/kg dw for total PCBs based on the dredging residuals methodology presented in Appendix B, Part 3A, of the FS.

Area 5

The fifth area includes 2.4 acres under the West Seattle Bridge and the bridge at the head of Slip 27 that have access restrictions (Figure 1). In these areas, removal is limited by geotechnical and structural considerations required to maintain stability of bridge columns. However, these areas are not limited in the amount of clean cover that could be placed following dredging. In addition, these areas experience little to no sediment disturbance from propwash. The resulting post-construction concentration was estimated to be 10 µg/kg dw for total PCBs through limited removal and RMC placement.

Area 6

The sixth area includes 1.8 acres under the three low bridges in the Sill Reach (Figure 1). These areas are characterized by extreme access limitations and widespread debris. Diver-assisted hydraulic dredging would be ineffective in these areas due to the presence of debris. Therefore, enhanced natural recovery (ENR) was assumed in these areas, with a post-construction concentration of 8 µg/kg dw, as a result of some dredging residuals depositing from adjacent areas consistent with the conceptual site model of sediment transport in the EW.

Based on the Port's analysis, considering all of these areas together, the site-wide SWAC immediately following construction was estimated to be 57 µg/kg dw for total PCBs, with an effective bioavailable concentration of 34 µg/kg. This analysis by Recognizing this evaluation has uncertainties inherent to modeling, under this hypothetical maximum

remediation scenario, the Port indicates, based on the assumptions (not all of which have been reviewed by EPA) and projections made and inputs considered, that post-construction SWAC would not achieve the natural-background-based SCO for total PCBs would not be achieved. As discussed above, there is a large amount of uncertainty associated with the estimated values for each area. In addition, this hypothetical SWAC assumes that construction would be completed uniformly across the site, at a single point in time (e.g., instantaneously), therefore, this analysis does not consider the sediment mixing and exchange or ongoing sediment deposition that would occur over the timeframe required to conduct this cleanup. Moreover, this hypothetical scenario may would have a construction timeframe of more than 15 years, during which time sediments would be mixing due to vessel propwash. Accordingly, the above site-wide post-construction SWAC represents, in the Port's view, an idealized condition that may not be realistically be achieved during remedy implementation.

4.1.2 Maintenance in the Long Term

This section describes threefour considerations by the Port for whether it would be technically possible to maintain the natural-background based SCOs for total PCBs and dioxin/furan in the long term, considering the lowest technically possible achievable concentration estimated in Section 4.1.1. The threefour considerations are as follows:

1. Predicted increase in the SWAC following sediment mixing and exchange between underpier and open-water sediment
2. Predicted future average concentrations in particulate matter entering the EW
3. Measured concentrations present in surface sediment at remediated sites proximal to the EW
4. Measured surface sediment concentrations in Elliott Bay

The first line of considerationevidence is the box model site-wide SWAC predictions. Following construction, box model predictions of the site-wide SWAC for each of the remediation alternatives except no action increase in the short-term (e.g., year 5 following construction) as a result of possible sediment mixing and exchange between open-water and underpier sediments (see FS Appendix J). The box model predicts that concentrations will then gradually reduce toward the net incoming sediment concentrations over time, which

are estimated to be above natural background-based cleanup levels and lowest technically possible achievable concentration for total PCBs and dioxins/furans (see next line of evidence). As indicated in FS Appendix J, the box model is based on a series of ~~assumption estimates~~ which were developed for the purposes of comparing alternatives. The ~~box~~ model output was particularly sensitive to certain input parameters, including the incoming Green-Duwamish sediment concentrations, bioavailability reductions from ~~activated~~ carbon treatment, and net sedimentation rates, all of which are ~~highly~~ uncertain.

The second line of ~~consideration evidence~~ is the estimated concentration of incoming sediments. Table 2 provides the estimated average sediment input concentrations for the EW based on incoming solids from both upstream (including Green River and LDW) and EW lateral inputs. These concentrations were calculated using a weighted average of chemical concentrations based on inputs entering the EW from the Green/Duwamish River, resuspended LDW bedded sediment, and lateral inputs from both the LDW and EW (see FS Table 5-5). ~~These estimates do not consider ongoing efforts to reduce sources of contamination to the upper Duwamish/Green River watershed, and thus are likely biased high.~~ Average input concentrations do not incorporate concentrations that may come from the EW bed, including the dredge residuals that will be present following construction, and sediments in unremediated areas. Average input concentrations were developed for the base case (best estimate), low bounding, and high bounding runs, adjusted to account for additional source control for lateral inputs (i.e., combined sewer overflow [CSO] and stormwater inputs) managed by source control programs (e.g., National Pollutant Discharge Elimination System [NPDES]), ~~which may have permit conditions modified in the future to reduce COC inputs to the EW.~~ ~~These estimates do not consider ongoing efforts to reduce sources of contamination to the upper Duwamish/Green River watershed.~~ For total PCBs, the average input concentrations ranged from 58 to 80-85 µg/kg dw, and for dioxin/furans the average input concentrations ranged from 2 to 8 ng TEQ/kg dw. The base case (best estimates) values for both total PCBs (42-45 µg/kg dw) and dioxins/furans (6 ng TEQ/kg dw) are well above the SCO concentrations for total PCBs (2 µg/kg dw), and marginally above the SCO for dioxins/furans (2 ng TEQ/kg dw). ~~NPDES permit conditions may be modified in the future to reduce COC inputs to the EW.~~

Commented [A5]: According to Table 5-5.

Commented [LR6]: All values in these last two sentences are from Table 5-5 using both upstream and EW lateral inputs. EPA edits were based only on Green River inputs.

The third line of considerationevidence is the post-remediation surface sediment concentrations of four cleanup sites in relatively close proximity to the EW, which were selected as representative of the post-remediation concentrations that could be expected to be achieved in the long term. Table 2 summarizes post-remediation monitoring data as of (insert date of most recent sampling data used for this analysis) for Pier 53-54, Lockheed Shipyard, Todd Shipyards, and Duwamish Diagonal (through 2012), as well as the form of remediation (dredging, capping, or ENR) used at each site. The surface sediment data range from 5 to 10 years post-remediation and represent the surface sediment concentrations that can be expected following dredging, capping, or ENR, as well as the influence of ongoing sedimentation from diffuse urban inputs. Mean concentrations from the above four datasets suggest that post-remediation concentrations in the EW could range from approximately 32 to 133 µg/kg dw for total PCBs, and be approximately 5 ng TEQ/kg dw for dioxin/furans (data from Duwamish/Diagonal cap only), depending on the dataset considered. These concentrations exceed the natural background levels for total PCBs and dioxins/furans. The resultant ranges of concentrations from all four of the datasets suggest that it is not technically possible to maintain the PRG for total PCBs (2 µg/kg dw) and may or may not be possible to maintain the PRG for dioxins/furans (2 ng TEQ/kg dw) in the long term in this region of Puget Sound, including the EW. It is important to note that these ranges do not incorporate ongoing and future source control efforts or sediment remediation in the surrounding area within the watersheds and may overestimate long-term decrease observed concentrations of depositing sediment. Furthermore, the sediment dynamics in the locations represented by these studies differ from those of the EW.

The fourth line of evidence is surface sediment concentrations from Elliott Bay. These data represent ambient concentrations in Elliott Bay, which provides an estimate of deposited sediment from diffuse urban inputs that may influence expected long-term concentrations. While the EW is adjacent to Elliott Bay, sediment load from Elliott Bay to the EW is assumed to be negligible compared to other sources (Windward and Anchor QEA 2014). Elliott Bay is a much larger waterbody than the EW and has many other sources along the shoreline that

Commented [A7]: Although these data appear in the LDW FS, they are taken out of context and were used for an entirely different purpose at LDW. For LDW, these data appear along with average PCB concentrations in other urban bays to provide information on general urban bay PCB concentrations at the time of the LDW FS was written. It was presented for informational purposes only and was not used in any way to support decision-making at LDW. It is inappropriately used here.

could contribute higher concentrations to sediment. As shown in Table 2, inner Elliott Bay⁷ samples had a mean total PCBs concentration of 153 µg/kg dw (2007 data), and the mean dioxins/furans concentration was 20 ng TEQ/kg dw (2007 data). Concentrations are higher when 90th percentile values are considered (274 µg/kg dw for total PCBs based on 2007 data). In outer Elliott Bay, mean total PCBs concentrations range from 28 µg/kg dw (2007 data) to 32 µg/kg dw (1991 to 2004 data), and the mean dioxins/furans concentration was 2 ng TEQ/kg dw (2007 data) (see Table 2). Concentrations are higher when 90th percentile values are considered (e.g., 53 µg/kg dw for total PCBs based on 2007 data). Post-remediation concentrations of total PCBs and dioxins/furans in sediment in the EW may be higher than these values because of its closer proximity to diffuse urban inputs, which are more represented by data from inner Elliott Bay.

In summary, all the three lines of consideration developed and analyzed by the Port to determine evidence that inform an evaluation of the concentrations that can be achieved in the long term in the EW indicate that the PRG will not likely be achieved or maintained. For total PCBs, the average concentrations are above the PRG of 2 µg/kg dw, and the range of achievable concentrations for all lines of consideration evidence is 9 to 153 µg/kg dw. For dioxins/furans, the average concentrations are above the PRG of 2 ng TEQ/kg dw, and the range of achievable concentrations for all lines of consideration evidence is 1.7 to 20 ng TEQ/kg dw. However, given that estimates do not include future source control actions in the Green/Duwamish watershed, the resulting values may be biased high. Regional background concentrations, if determined, may fall within these ranges.

4.2 Net Adverse Environmental Impact

The second factor in determining an upward adjustment of the SCO-based cleanup level is the determination of net adverse impact on the aquatic environment, which takes into account “the short- and long-term positive effects on natural resources, habitat restoration, and habitat enhancement and the short- and long-term adverse impacts on natural resources and habitat caused by cleanup actions” (WAC 173-204-560(2)(a)(ii)(B)). This discussion

⁷ Inner Elliott Bay samples are generally defined as samples east of a line from Terminal 91 directly south to West Seattle. Outer Elliott Bay includes the samples west of the line. See the depiction in Appendix I, Figure I-3, of the LDW FS (AECOM 2012).

represents some encompasses certain hypothetical future scenarios and possible lines of consideration evidence that could be used as part of a net environmental impacts analysis. It and is presented by the Port for comparison purposes only. EPA disagrees with the assumptions made in this analysis and it is not required to be used for EPA decision-making.

The SMS cleanup levels for total PCBs and dioxin/furans that are not adjusted significantly upward from the PRG could only be met and reliably maintained with additional dredging over larger areas and at greater depths, and repeated capping and redredging of the same areas as concentrations rise due to diffuse source inputs over time. This approach would result in very large adverse impacts on the aquatic environment (natural resources and habitat) from construction without producing any countervailing long-term environmental benefits from the additional cleanup measures (i.e., risk reduction). Repeated rounds of dredging and/or capping would result in major additional construction-related adverse impacts to the benthic community, due to disruption of the established biological active zone, and to fish tissue contaminant levels, due to releases of contaminated material during dredging, resulting in higher fish exposures. In addition, these adverse impacts would occur over a significantly longer period of time. Even with ongoing efforts of this type, evidence presented in Section 4.1 of this appendix suggests that the PRGs for total PCBs and dioxin/furans would still not be achieved. As such, the continued cleanup activities in an attempt to reach concentrations closer to the PRG would result in significant adverse impacts to the environment without commensurate benefits to the benthic community or reductions in tissue concentrations that would lower human health risks. Ultimately, the EW system will equilibrate to incoming sediment concentrations that are estimated to be higher than the PRG and similar to concentrations resulting from less disruptive cleanup activities associated with higher cleanup levels (e.g., CSL).

In comparison, the SMS cleanup levels based on the CSL for total PCBs and dioxin/furans (i.e., regional background, if established) would result in slightly smaller adverse impacts on the aquatic environment from construction because the cleanup technologies needed to meet the cleanup levels would be less intrusive to benthic communities in some areas (less dredging or capping), and the need for additional contingency actions would be greatly reduced or eliminated. A cleanup level at or close to a potential regional background concentration for total PCBs and dioxin/furans, if established, would reflect the

concentrations of those contaminants in incoming sediment over the long term, thereby avoiding unnecessary adverse impacts on the aquatic environment from construction and ultimately resulting in similar or improved long-term environmental benefits from cleanup (i.e., risk-reduction). Therefore, sediment cleanup levels based on the PRG will result in net adverse impacts, which would likely not occur with cleanup levels that are adjusted upward to the CSL based on regional background.

4.3 Summary and Conclusion

This Port analysis indicates that compliance with the SMS and CERCLA PRGs would likely involve the adjustment of cleanup levels upward from the PRG-SCO (PRG) to the CSL for total PCBs and dioxins/furans. This adjustment may occur in the future if the CSL (i.e., a regional background value suitable for use at applicable to the EW Superfund site) is established by EPA for these contaminants.

For FS purposes, a hypothetical maximum removal remediation scenario was analyzed to approximate lowest technically possible concentrations for total PCBs that could be achieved following construction. While this analysis by the Port is subject to uncertainty, it indicated that approximately 57 µg/kg dw could be achieved (34 µg/kg when making adjustments for bioavailability) when considering limitations to remediating near structures to achieve very low total PCBs concentrations.

Multiple lines of consideration evidence were analyzed by the Port evaluated to approximate values that could be achieved in the long term. For total PCBs, the average concentrations are above the PRG of 2 µg/kg dw, and the range of achievable concentrations for all lines of evidence is 9 to 153 µg/kg dw. For dioxins/furans, the average concentrations are above the PRG of 2 ng TEQ/kg dw, and the range of achievable concentrations for all lines of consideration evidence is 1.7 to 20 ng TEQ/kg dw. As discussed in Section 4, under the SMS, the cleanup level may not be adjusted above the CSL (i.e., regional background values, if established by EPA).

Finally, a hypothetical possible scenario for considering the net adverse environmental impact for setting the cleanup level at the SCO was qualitatively discussed by the Port,

indicating that the cleanup levels would likely need to be adjusted upward to the CSL, if established, to avoid environmental disturbances that results in no environmental benefit.

As noted above, this analysis was developed by the Port for FS purposes only; it contains numerous assumptions about future conditions that cannot be reliably estimated at this time. It is inherently uncertain. While CERCLA does not require that a technical possibility evaluation be conducted in the FS, it provides additional information that EPA could consider for EPA decision-making, including establishing PRGs or a potential future adjustment of cleanup levels. Technical possibility will be determined based on empirical long-term monitoring data for the selected alternative to comply with the SMS, or TI waiver.

5 SEDIMENT RECOVERY ZONE

Under the SMS, an Ecology-approved restoration timeframe of longer than 10 years (i.e., cleanup levels not achieved within 10 years) would result in the designation of an SRZ (WAC 173-204-590(5)(b)). The SMS define the SRZ as the following:

“Sediment recovery zone” means an area authorized by the department within a site or sediment cleanup unit where the department has determined the cleanup action cannot achieve the applicable sediment cleanup standards within ten years after completion of construction of the active components of the cleanup action.

Designation of an SRZ is accomplished through a process administered by Ecology. An absolute restoration timeframe of 10 years or more as Ecology would establish under the SRZ provisions of the SMS is not necessarily more stringent than CERCLA requirements, thus, an SRZ is not an ARAR under CERCLA. EPA may consider the substantive criteria for an SRZ, WAC 173-204-590(3), when determining the length of time for completion of the remedial action for the EW. The remaining portion of the discussion of SRZs under the SMS is presented by the Port for comparison purposes only and has no bearing on EPA decision-making for the EW.

The SRZ is used to track a cleanup area that remains above cleanup levels and perform additional cleanup or source control actions as necessary. The requirements of the SRZ are listed in WAC 173-204-590(2), and are very similar to the CERCLA requirements of the for a selected remedy. EPA may consider the substantive criteria for an SRZ, WAC 173-204-590(3), when determining the reasonable restoration timeframe of the remedial action for the EW. The remaining portion of the discussion of SRZs under the SMS is presented for comparison purposes only.

The key components of the SRZ approach, if used, are the following:

- The SRZ could be designated side-wide for relevant human health risk drivers 10 years following construction.
- 5-year reviews and site-wide monitoring program could provide the periodic review process for adjusting, eliminating, or renewing the SRZ consistent with the SMS.

- The SRZ could be used in concert with active cleanup and source control measures for the selected alternative, and would not replace cleanup actions. The contaminant concentrations within the SRZ will be as close as practicable to the cleanup level, based on the CERCLA comparison of alternatives under the nine criteria in the FS.

Post-construction site-wide monitoring data may will be used to evaluate progress toward meeting the cleanup levels. This information could also be used to support establishment or evaluation of regional background concentrations and potential modification of the SRZ, and closure of the .

If monitoring data shows cleanup standards cannot be met, the following options are available for Ecology to consider:

- 1. If noncompliance is due to PLP sources not being controlled, additional source control may be necessary.*
- 2. If noncompliance is due to contribution from other sources that are not under the responsibility or authority of the PLP, closure of the SRZ may be appropriate or adjustment of the cleanup level may be appropriate. For example:*
 - a. Ecology may consider whether the cleanup level should be adjusted upwards according to the process detailed in Chapter 7, Section 7.2.3. An example of when this may be appropriate is where the cleanup level was established below regional background, but Ecology has since established or approved regional background for the geographic area where the site is located. In this case, Ecology may determine that regional background represents the concentration in sediment that is technically possible to maintain, due to ongoing sources that are not under the authority or responsibility of the PLP. Therefore, Ecology could allow upwards adjustment of the sediment cleanup level to the CSL if regional background has been established as the CSL.*
 - b. If the cleanup levels are based on background (regional or natural), Ecology will consider whether background concentrations have increased and the cleanup level should be adjusted upwards.*

(Ecology 2017, Section 14.2.6)

6 CONCLUSIONS

The PRGs in the EW FS have been developed under CERCLA to be consistent with the SMS (WAC 173-204-560). The selected alternative will meet the SMS ARAR over time in one of two ways: 1) by achieving the SCO; in a reasonable restoration timeframe, ~~as determined by EPA~~; or 2) by achieving the cleanup level in a reasonable restoration timeframe, ~~as determined by EPA~~ after the establishment of a CSL and upward adjustment of the cleanup level. If cleanup levels are not achieved ~~within a reasonable restoration timeframe following construction~~, additional time for achieving the cleanup levels ~~SMS ARAR~~ may be warranted under CERCLA if determined to be appropriate by EPA. In that instance, ~~met through compliance with~~ the substantive criteria of an SRZ (WAC 173-204-590(3)) could be considered by EPA), potentially including determination by EPA of whether an extension of the restoration timeframe is appropriate.

Formatted: Strikethrough, Highlight

Formatted: Font color: Red

Because it is not known whether, or to what extent, the SMS ARARs for various COCs will be achieved in the long term, or the timing of a potential regional background evaluation, ~~it is not possible to definitively determine SMS compliance at this time the way in which the cleanup will comply with SMS (described above as meeting either the natural background PRG in a reasonable restoration timeframe, or by upwardly adjusting the cleanup level to regional background and meeting it in a reasonable restoration timeframe, is not selected at this time.~~ The method used to comply with the SMS ARAR will depend primarily on the timing of regional background evaluations for the EW and measured ~~performance following construction.~~

EPA may also issue a TI waiver at some point in the future if EPA determines that the SMS-based cleanup levels cannot be practicably achieved within the EW-based on long-term monitoring data and trends. This would be conducted either as part of a ROD Amendment or an ESD.

7 REFERENCES

- AECOM, 2012. Feasibility Study, Lower Duwamish Waterway, Seattle, Washington. Final Report. Prepared for Lower Duwamish Waterway Group. October 2012.
- Ecology (Washington State Department of Ecology), 2008. Dioxins, Furans, and other Contaminants in Surface Sediment and English Sole Collected from Greater Elliott Bay (Seattle), Publication No. 08-03-017. June 2008.
- Ecology, 2017. Sediment Cleanup User's Manual II. Guidance for Implementing the Cleanup Provisions of the Sediment Management Standards, Chapter 173-204 WAC. Publication No. 12-09-057. April 2017.
- EPA (U.S. Environmental Protection Agency), 2002. Role of Background in the CERCLA Cleanup Program. Office of Solid Waste and Emergency Response. U.S. Environmental Protection Agency, Washington, D.C., OSWER Directive 9285.6-07P. April 26, 2002.
- Floyd|Snider, 2010. Subject: Requested 5-Year Review Package—Todd Shipyards Sediment Operable Unit. Project Number: Todd-NPL. Letter to Lynda Priddy, U.S. Environmental Protection Agency, Region 10. August 31, 2010.
- King County, 2010. Pier 53-55 Sediment Cap and Enhanced Natural Recovery Area Remediation Project, 2002 Data and Final Report, King County. June 2010.
- Tetra Tech, 2012. Lockheed Shipyard No. 1, Sediments Operable Unit (LSSOU) Harbor Island, Seattle, Washington, 2012 Operations, Monitoring and Maintenance Report. Prepared for Lockheed Martin Corporations. Prepared by Tetra Tech. September 2012.
- Windward and Anchor QEA, 2014. Supplemental Remedial Investigation. East Waterway Operable Unit Supplemental Remedial Investigation/Feasibility Study. Final. January 2014.

TABLES

FIGURES
